

Technical Data

WSA 360		WSA-360	WSA-360SL	WSA-360FC
Cooling Capacity	kW	845	780	822
Power Consumption		271	283	283
Working limits ambient temperature	°C	-18* / +46	-18* / +46	-18* / +46
Working limits water outlet temperature	°C	-5* / +25	-5* / +25	-5* / +25
Refrigerant	Type	R134a	R134a	R134a
Power supply	V/ph/Hz	400 / 3 / 50	400 / 3 / 50	400 / 3 / 50
Secondary power supply	Vac	230	230	230
Max. power consumption	kW	706	706	706
Max. absorbed current	A	387	387	387
Starting current	A	861	861	861
Height x width x depth	mm	2473 x 2278 x 4240	2473 x 2278 x 4240	2473 x 2278 x 4240
Noise level	dB(A)	70,8	70,8	70,8
Compressor				
Cooling Circuit	n°	2	2	2
Semi-Hermetic Double Screw compressor	n°	2	2	2
Partialization	%	12,5...100	12,5...100	12,5...100
Max. power consumption	kW	350	350	350
Max. absorbed current	A	620	620	620
Power consumption W7L35	kW	239	239	251
Absorbed current W7L35	A	376	376	393,0
Fans				
Axial fans	n°	16	16	16
Fan flow	m³/h	278715	186770	224542
Max. Power consumption	kW	35,2	35,2	35,2
Max. absorbed current	A	75,7	75,7	75,7
Power Consumption W7L35	kW	32	20	32
Absorbed Current W7L35	A	68,8	40	68,8
Hydraulic				
Coolant liquid	Type	Water		
Inlet temperature	°C	12	12	12
Outlet temperature	°C	7	7	7
Water flow	m³/h	145	134	145
Pressure drops	kPa	32	28	32,24
Water connections	Inches	8	8	8
FC				
Cooling capacity W10L(see below)	kW	-	-	835
Temperature of total FC	°C	-	-	-1,5
Flow of fluid to be cooled	m³/h	-	-	144
Pressure drop	kPa	-	-	52
EER				
EER		3,12	2,75	2,91
ESEER (ISO14511)		4,76	4,78	4,55
IPLV		4,6	4,68	4,46

Evaporator water (in/out) 12/7 °C; condenser air (in) 35 °C;
 Average sound pressure level at 10 m distance; unit in a free field on a reflective surface.
 According to ISO 3744. Unit at full capacity. Pump contribution is not considered.
 *In case of applications with an output fluid temperature below +5 °C, please contact the manufacturer.

FC

30% Glycol-Water solution. Evaporator solution IN/OUT= 15/10 °C; Condenser air 30 °C
 Average sound pressure level, at 10m distance, unit in a free field on a reflective surface.
 Unit at full capacity. According to ISO 3744. Pumps contribution is not considered.
 * In case of applications with output fluid temperature below 0°C, please contact the manufacturer